

SURFACE PREPARATION Substrates must be structurally stable. Surfaces must be free from material that would inhibit bonding. Floor level cannot exceed a variance of 3/16"/10'. Moisture test all concrete subfloors in accordance with ASTM F1869 or ASTM F2170. **INSTALLATION** Apply adhesive using the proper trowel. Requires ~1hr dry time or dry to the touch before installation. Follow flooring manufacturer's recommendations. Do not install into wet adhesive. Scan the QR Code for further instructions.

OVER POROUS SUBSTRATES Sheet flooring requires 20mins open time before installing.

OVER NON-POROUS SUBSTRATES Floor must be installed within 2hrs after adhesive is dry.

ADDITIONAL INSTRUCTIONS Lift flooring periodically to ensure 100% transfer. Limit foot traffic for 24hrs after installation. Restrict moving heavy objects for 48hrs. Store unopened containers no longer than 1yr.

CLEAN-UP Wet adhesive may be cleaned using a wet rag. For dried adhesive, use mild solvent sparingly with a clean, white, cotton cloth. Do not pour solvent directly on flooring.

GripWise™

ADHESIVES PS-004

PRESSURE SENSITIVE

- ▶ LUXURY VINYL TILE/PLANK/UNDERLAYMENT
- ▶ VINYL/NON-VINYL BACKED CARPET TILE
- ▶ CARPET CUSHION SUBSTRATE
- ▶ FIBERGLASS BACK OR VINYL SHEET



TROWELS AND COVERAGE		
Floor Product	Trowel	Coverage
Porous Substrates		150-200 ft ² /gal.
	1/16" x 1/16" x 1/16" SQ NOTCH	
Non Porous Substrates Carpet Tile		250-300 ft ² /gal.
	1/16" x 1/32" x 1/32" U NOTCH	
Carpet Tile Sheet Vinyl LVP Underlayment		250-300 ft ² /gal.
	3/8" Nap Roller	

PROFESSIONAL GRADE

4 GALLONS

PS-004 is a solvent-free pressure sensitive adhesive formulated for the installation of vinyl-backed carpet tile and dimensionally stable vinyl tile, plank and LVP underlayment. It may be used as a releasable or permanent adhesive. If flooring is installed while PS-004 is still wet a permanent bond will be formed. PS-004 is nonstaining. It resists plasticizer migration and development of mold and mildew. Its VOC Content is <3.4g/l with a pH of 7.0-9.0 and density of 8lbs/gal.

RESTRICTIONS Indoor use only. Protect from freezing. Do not install over adhesive residues. PS-004 is not a moisture barrier. MVER must not exceed 5lbs/1,000sqft/24hrs or 80%RH on existing slabs and must not exceed 8lbs/1,000sqft/24hrs or 90%RH on green slabs. Do not exceed the flooring manufacturer's moisture limits. Install when temperature is 60°F-95°F. Substrate temperature must be 50°F-90°F. Acclimate Flooring according to its manufacturer. Do not wet clean the installation for 2wks.

CAUTION Use in ventilated areas, wear protective gear to avoid contact with skin, eyes and airway. **EMERGENCY PROCEDURES** SEEK MEDICAL ATTENTION IF ACCIDENTAL INGESTION. Do not induce vomiting. Wash Skin thoroughly with soap and water. Flush eyes with water for 15 minutes. Keep this and all other adhesives away from children and pets.

Wise Products, LLC
635 Old Hickory Blvd. Nashville, TN 37138
Phone: (615) 847-2919
Internet: www.wiseflooringproducts.com
Limited Warranty

