

### POLYETHYLENE FOAM FLOOR PROTECTOR

SoundWise™ **FG 1220** is specifically designed to protect your floors and any other products while under construction. **FG 1220** stays put under heavy use and construction conditions. The ribbed profile allows the floor to breathe not to damage finish. FG 1220 can be used vertically or horizontally protecting any and all areas of new home construction and existing home renovations.

#### APPLICATION:

- Commercial
- Residential

#### PRODUCT FEATURES:

- Anti-Microbial
- Recyclable
- MADE IN THE USA
- One Year Limited Warranty

#### APPROVED FOR USE OVER:

- Laminate
- Solid Hard Wood Floating Floors
- Engineered Wood Floating Floors
- WPC, SPC, LVP and Rigid Core
- Ceramic

#### PHYSICAL CHARACTERISTICS:

- Material = Polyethylene Foam
- Density (lbs./cu ft) = 1.2
- Thickness (mm) = 2.0
- Joining System = none

#### DIMENSIONS AND PACKAGING:

- Roll Size = 600 sq ft
- Roll Dimensions = 48" x 150'
- Rolls Per Pallet =
- Pallets Per Truck = 240
- Rolls Per Truck =

#### INSTALLATION INSTRUCTIONS:

1. Clean, sweep or vacuum floor of all debris.
2. Check that the floor is clean, dry and level.
3. Roll out overlay to length of room, slightly overlapping each row.
4. Tape seams together with polypropylene packaging or duct tape.



"Working with ExxonMobil and use of their performance polymers has been key to the successful development of this unique product."

*Ron Wise – Owner, Wise Manufacturing*



## ExxonMobil

Vistamaxx™  
Performance Polymers

SoundWise™ Underlayment for all your residential and commercial flooring needs.



**WISE PRODUCTS, LLC**  
635 Old Hickory Blvd  
Nashville, TN 37138

[www.wiseflooringproducts.com](http://www.wiseflooringproducts.com)  
PH (615) 847-2919  
Fax (615) 847-2425

Manufactured by:  
**WISE MANUFACTURING, INC**  
ISO-9001 / IATF - 16949 REGISTERED