

POLYETHYLENE PERIMETER BARRIER STRIP

SoundWise™ **PBS 1560** is perimeter barrier strip designed to isolate the flooring perimeter when grouting floors, use as a sound isolation barrier or to accomplish an expansion joint around the perimeter of your flooring. **PBS 1560** stays put under heavy use and construction conditions. PBS 1560 is easily installed.

APPLICATION:

- Commercial
- Residential

PRODUCT FEATURES:

- Helps with Perimeter Spacing
- Eliminates Hard Grouting
- Sound Abatement
- Recyclable
- MADE IN THE USA
- One Year Limited Warranty

APPROVED SUBSTRATES:

- Cured Concrete
- APA Grade Plywood
- OSB
- APA Approved Interior Subfloors

PHYSICAL CHARACTERISTICS:

- Material = Polyethylene Foam
- Density (lbs./cu ft) = 1.5
- Thickness (in) = .25
- Joining System = none

DIMENSIONS AND PACKAGING:

- Roll Size = 125 ft
- Roll Width = 4 in
- Roll Dimensions =
- Rolls Per Pallet = 80
- Pallets Per Truck = 26
- Rolls Per Truck = 2080

INSTALLATION INSTRUCTIONS:

Floor Installation-

1. Clean, sweep or vacuum floor of all debris.
2. Check that the floor is clean, dry and level.
3. Place PBS vertically against the perimeter of floor.
4. Lay flooring to the PBS.
5. Check that 1/4" expansion joint around the perimeter of the floor has been accomplished.

Installation for Sound Abatement-

1. Clean, sweep or vacuum floor of all debris.
2. Remove any baseboards from the perimeter of the flooring.
3. Place PBS vertically against the perimeter of floor.
4. Reinstall the baseboards.



"Working with ExxonMobil and use of their performance polymers has been key to the successful development of this unique product."

Ron Wise – Owner, Wise Manufacturing



ExxonMobil

Vistamaxx™
Performance Polymers

SoundWise™ Underlayment for all your residential and commercial flooring needs.



WISE PRODUCTS, LLC

635 Old Hickory Blvd
Nashville, TN 37138

www.wiseflooringproducts.com

PH (615) 847-2919
Fax (615) 847-2425

Manufactured by:
WISE MANUFACTURING, INC
ISO-9001 / IATF - 16949 REGISTERED