

POLYETHYLENE FOAM UNDERLAYMENT

SoundWise™ PE 1515 is an economy grade laminate and wood flooring foam underlayment that provides moisture protection, sound control and warmth. PE 1515 can be purchased with LAPWISE™ seam sealing technology or with lip and tape. PE 1515 protects the life of your floor.



APPROVED SUBSTRATES:

- Cured Concrete
- APA Grade Plywood
- OSB

PHYSICAL CHARACTERISTICS:

- Material = Polyethylene Foam (non-xlink)
- Density (lbs./cu ft) = 1.5
- Thickness (mm) = 1.5
- Joining System = LAPWISE™ Technology or lip and tape

DIMENSIONS AND PACKAGING:

- Roll Size = 100.1 sq ft
- Roll Dimensions = 42" x 28.6'
- Rolls Per Pallet = 120
- Pallets Per Truck = 26
- Rolls Per Truck = 3536

INSTALLATION INSTRUCTIONS:

1. Clean, sweep or vacuum subfloor of all debris.
2. Check subfloor. Should be clean, dry and level.
3. Roll out underlayment to length of room.
4. If below grade, extend up the wall 2".
5. Join seam together. DO NOT overlap seams.
6. Underlayment with lip and tape- join seams together, overlap the film lip and attach to the adhesive bead. Remove tape release liner before applying film lip. For LAPWISE™ seam sealing technology, when rolling out second row, overlap LAPWISE™ seam 2". Remove release liner and press LAPWISE™ seam together.

APPLICATION:

- Residential



PRODUCT FEATURES:

- Economical
- Moisture Protection
- LAPWISE™ seam sealing technology or lip and tape.
- Ease of Installation
- Comfort
- Recyclable
- Sound Abatement
- MADE IN THE USA
- One Year Limited Warranty

APPROVED FOR USE UNDER:

- Laminate
- Bamboo Floating Floors
- Solid Hard Wood Floating Floors
- Engineered Wood Floating Floors

"Working with ExxonMobil and use of their performance polymers has been key to the successful development of this unique product."

Ron Wise – Owner, Wise Manufacturing



ExxonMobil

Vistamaxx™
Performance Polymers

SoundWise™ Underlayment for all your residential and commercial flooring needs.



WISE PRODUCTS, LLC
635 Old Hickory Blvd
Nashville, TN 37138

www.wiseflooringproducts.com
PH (615) 847-2919
Fax (615) 847-2425

Manufactured by:
WISE MANUFACTURING, INC
ISO-9001 / IATF - 16949 REGISTERED