

SoundWise™

FG1220

FOR RESIDENTIAL OR COMMERCIAL PROJECTS

POLYETHYLENE FOAM FLOOR PROTECTOR

USE FG1220 OVER

Solid Hard Wood Floors
 Engineered Wood Floors
 LVP, WPC, SPC and Laminate

Laminate
 Ceramic

- # ANTI-MICROBIAL
- # RIBBED PROFILE
- # EASE OF INSTALLATION

"Working with ExxonMobil and use of their performance polymers has been key to the successful development of this unique product."

Ron Wise – Owner, Wise Manufacturing



ExxonMobil

Vistamaxx™
 Performance Polymers



Installation Instructions Clean, sweep or vacuum subfloor of all debris. Check that the floor is clean, dry and level. Roll out overlay to length of room slightly overlapping each row. Tape seams together with polypropylene packaging or duct tape.

Find Out More About Our Products

support@wiseflooringproducts.com

www.wiseflooringproducts.com

(615) 847-2919



PHYSICAL CHARACTERISTICS

MATERIAL	DENSITY	THICKNESS	WARRANTY	Width	JOINING SYSTEM
Polyethylene Foam	1.2lbs/ft ³	2mm	Limited 1 year	48"	NONE

48" x 150' (600 ft²)