

# SoundWise™

## PP4015

FOR RESIDENTIAL OR COMMERCIAL PROJECTS

### LOW PROFILE FOAM UNDERLAYMENT



#### USE PP4015 UNDER

Solid Hard Wood Floating Floors  
 Engineered Wood Floating Floors  
 LVP, WPC, SPC and Laminate  
 Rigid Core MLF (3.2mm+)  
 Double Glue Installations

#### APPROVED SUBSTRATES

Cured Concrete  
 APA Grade Plywood  
 APA Approved Interior Subfloors  
 OSB

### # SOUND ABATEMENT

### # MOISTURE PROTECTION (75%RH)

### # LAPWISE™ SEAM SEALING TECHNOLOGY

"Working with ExxonMobil and use of their performance polymers has been key to the successful development of this unique product."

*Ron Wise – Owner, Wise Manufacturing*



**ExxonMobil**

Vistamaxx™  
 Performance Polymers



**INSTALLATION INSTRUCTIONS** Clean, sweep or vacuum subfloor of all debris. Check that the subfloor is clean, dry and level. Roll out underlayment to length of room. If below grade, extend up the wall 2". Roll out second row overlap LAPWISE™ seam 2". Remove release liner and press LAPWISE™ seam together.

Find Out More About Our Products

support@wiseflooringproducts.com

www.wiseflooringproducts.com

(615) 847-2919



SOUND TEST					
IIC	STC	DELTA	FLOOR	SUBFLOOR	
IMPACT ISOLATION	SOUND TRANSMISSION	FULL ASSEMBLY	(COVERING)		
66	63	26	LVP	CONCRETE	
PHYSICAL CHARACTERISTICS					
MATERIAL	DENSITY	THICKNESS	COMPRESSION STRENGTH	MOISTURE VAPOR EMISSIONS RATE	JOINING SYSTEM
Polypropylene Foam (non-xlink)	4lbs/ft <sup>3</sup>	1.5mm	16.1 (psi@50%)	.000003389lbs/m <sup>2</sup> /24h	LAPWISE™ TECHNOLOGY
42" x 28.6' (100.1 ft <sup>2</sup> )					

Limited 20yr Warranty