

# SoundWise™

## PP5010

FOR RESIDENTIAL OR COMMERCIAL PROJECTS

### PREMIUM BLACK LVT UNDERLAYMENT

**APPROVED UNDER:**  
FOAM/ATTACHED  
BACKED FLOORING

#### USE PP5010 UNDER

LVP, WPC, SPC and Laminate  
Rigid Core MLF (3.2mm+)  
Solid Hard Wood Floating Floors  
Engineered Wood Floating Floors  
Bamboo Floating Floors  
Double Glue Installations

#### APPROVED SUBSTRATES

Cured Concrete  
APA Grade Plywood  
APA Approved Interior Subfloors  
OSB

# SOUND ABATEMENT

# MOISTURE PROTECTION (85%RH)

# LAPWISE™ SEAM SEALING TECHNOLOGY

"Working with ExxonMobil and use of their performance polymers has been key to the successful development of this unique product."

*Ron Wise – Owner, Wise Manufacturing*



**ExxonMobil**

Vistamaxx™  
Performance Polymers



**INSTALLATION INSTRUCTIONS** Clean, sweep or vacuum subfloor of all debris. Check that the subfloor is clean, dry and level. Roll out underlayment to length of room. If below grade, extend up the wall 2". Roll out second row overlap LAPWISE™ seam 2". Remove release liner and press LAPWISE™ seam together.

Find Out More About Our Products

support@wiseflooringproducts.com  
www.wiseflooringproducts.com  
(615) 847-2919



#### SOUND TEST

IIC IMPACT ISOLATION	STC SOUND TRANSMISSION	DELTA	FLOOR (COVERING)	SUBFLOOR
69	61	27	LVP	6" CONCRETE

#### PHYSICAL CHARACTERISTICS

MATERIAL	DENSITY	THICK- NESS	COMPRESSION STRENGTH	MOISTURE VAPOR EMISSIONS RATE	JOINING SYSTEM
Polypropylene Foam	5lbs/ft³	1mm	20.2 (psi@50%)	.000003389lbs/ m²/24h	LAPWISE™ TECHNOLOGY

42" x 28.6' (100.1 ft²)

Limited 20yr Warranty