

# SoundWise™

LOW PROFILE HIGH DENSITY **PP3020**

FOR RESIDENTIAL OR COMMERCIAL PROJECTS

## PREMIUM FOAM UNDERLAYMENT



### USE PP3020 UNDER

Laminate  
Bamboo Floating Floors  
Solid Hard Wood Floating Floors  
Engineered Wood Floating Floors  
Double Glue Installations

### APPROVED SUBSTRATES

Cured Concrete  
APA Grade Plywood  
OSB

- # SOUND ABATEMENT
- # MOISTURE PROTECTION (75%RH)
- # LAPWISE™ SEAM SEALING TECHNOLOGY

"Working with ExxonMobil and use of their performance polymers has been key to the successful development of this unique product."

*Ron Wise – Owner, Wise Manufacturing*



**ExxonMobil**

Vistamaxx™  
Performance Polymers



**INSTALLATION INSTRUCTIONS** Clean, sweep or vacuum subfloor of all debris. Check that the subfloor is clean, dry and level. Roll out underlayment to length of room. If below grade, extend up the wall 2". Roll out second row overlap LAPWISE™ seam 2". Remove release liner and press LAPWISE™ seam together.

Find Out More About Our Products  
support@wiseflooringproducts.com  
www.wiseflooringproducts.com  
(615) 847-2919



SOUND TEST					
IIC	STC	DELTA	FLOOR	SUBFLOOR	
IMPACT ISOLATION	SOUND TRANSMISSION	FULL ASSEMBLY	(COVERING)		
67	63	26	LVP	CONCRETE	
PHYSICAL CHARACTERISTICS					
MATERIAL	DENSITY	THICKNESS	COMPRESSION STRENGTH	MOISTURE VAPOR EMISSIONS RATE	JOINING SYSTEM
Polypropylene Foam (non-xlink)	3lbs/ft <sup>3</sup>	2mm	13.6 (psi@50%)	.00000338lbs/m <sup>2</sup> /24h	LAPWISE™ TECHNOLOGY
42" x 28.6' (100.1 ft <sup>2</sup> )					

Limited 20yr Warranty