

# SoundWise™ PP 3020

## PREMIUM FOAM UNDERLAYMENT



SoundWise™ PP 3020 is specifically built to address today's challenging floating floor installations. This premium foam underlayment is a waterproof non-cross linked technology that can be used under all laminate and hardwood floating floors. This Premium Underlayment provides moisture protection, sound abatement, and overall high density stability. It has the highest Delta rating in the industry in this category.

**APPLICATION:** Approved for commercial and residential flooring.

### DIMENSIONS AND PACKAGING:

- Roll Size = 100.1 sq ft
- Roll Dimensions = 42" x 28.6'

### PHYSICAL PROPERTIES:

- Material = Polypropylene Foam (non-xlink)
- Density (lbs./cu ft) = 3.0
- Thickness (mm) = 2.0
- Compression Strength (psi@50%) = 13.6
- Moisture Vapor Emissions Rate = 0.00000338 (lbs/m2/24hrs)
- Joining System is LapWise™ Technology

### INSTALLATION INSTRUCTIONS:

1. Clean, sweep or vacuum subfloor of all debris.
2. Check subfloor. Should be clean, dry and level.
3. Roll out underlayment to length of room.
4. If below grade, extend up the wall 2".
5. Roll out second row, overlap LapWise™ seam 2".
6. Remove release liner and press LapWise™ seam together.

### SOUND TEST:

IIC	STC	DELTA	FLOOR	SUBFLOOR
67	63	26	LVP	6" CONCRETE w/ CEILING

### APPROVED FOR USE UNDER:

- Laminate
- Solid Hardwood Floating Floors
- Engineered Wood Floating Floors
- Bamboo Floating Floors

### APPROVED SUBSTRATES:

- OSB
- Cured Concrete
- APA Approved Interior Subfloors

### PRODUCT FEATURES:

- Sound Abatement
- Moisture Protection up to 75% RH
- LapWise™ Seam Sealing Technology
- Recyclable
- 20-Year Limited Warranty
- Made in the USA



**ExxonMobil**  
Vistamaxx™  
Performance Polymers



# Wise Products, LLC

**Website:** [www.WiseFlooringProducts.com](http://www.WiseFlooringProducts.com)

**Phone:** 615-847-2919

**Fax:** 615-847-2425

**Email:** [Sales@WiseFlooringProducts.com](mailto:Sales@WiseFlooringProducts.com)

**RATED RESIDENTIAL AND COMMERCIAL**