

# SoundWise™

**PP 4015**

## LOW PROFILE UNDERLAYMENT

### PRODUCT FEATURES:



Sound Abatement



Moisture Protection



20-Year Limited Warranty



### INSTALLATION INSTRUCTIONS:

1. Clean, sweep or vacuum subfloor of all debris.
2. Check subfloor. Should be clean, dry and level.
3. Roll out underlayment to length of room.
4. If below grade, extend up the wall 2".
5. Roll out second row, overlap LapWise™ seam 2".
6. Remove release liner and press LapWise™ seam together.



FLOAT IT



NAIL IT



GLUE IT

### APPROVED FOR USE UNDER:

- Laminate
- WPC, SPC, LVP and Rigid Core
- Glue Down LVP\*
- Solid & Engineered Floating Floors

*\*Acrylic Pressure Sensitive Adhesives Only*

### APPROVED SUBSTRATES:

- OSB
- Cured Concrete
- APA Approved Interior Subfloors



**ExxonMobil**  
Vistamaxx™  
Performance Polymers

Wise Products, LLC

Website: [www.WiseFlooringProducts.com](http://www.WiseFlooringProducts.com)

Phone: 615-847-2919

Fax: 615-847-2425

Email: [sales@wisemanufacturing.com](mailto:sales@wisemanufacturing.com)

**RATED RESIDENTIAL AND COMMERCIAL**