

SoundWise™ PP 5010

PREMIUM UNDERLAYMENT



SoundWise™ PP 5010 is specifically designed for both floating and glue down resilient and composite floors. It excels in sound control and high moisture applications. With non-crosslinking technology, this underlayment is guaranteed moisture resistant up to 85% RH. This foam underlayment has the highest Delta rating in its category for sound abatement.

APPLICATION: Approved for commercial and residential flooring.

DIMENSIONS AND PACKAGING:

- Roll Size = 100.1 sq ft
- Roll Dimensions = 42" x 28.6'

PHYSICAL PROPERTIES:

- Material = Polypropylene Foam (non-xlink)
- Density (lbs./cu ft) = 5.0
- Thickness (mm) = 1.0
- Compression Strength (psi@50%) = 20.2
- Moisture Vapor Emissions Rate = 0.000003389 (lbs/m2/24hrs)
- Joining System is LapWise™ Technology

INSTALLATION INSTRUCTIONS:

1. Clean, sweep or vacuum subfloor of all debris.
2. Check subfloor. Should be clean, dry and level.
3. Roll out underlayment to length of room.
4. If below grade, extend up the wall 2".
5. Roll out second row, overlap LapWise™ seam 2".
6. Remove release liner and press LapWise™ seam together.

SOUND TEST:

IIC	STC	DELTA	FLOOR	SUBFLOOR
69	61	27	LVP	6" CONCRETE w/ CEILING

APPROVED FOR USE UNDER:

- WPC, SPC, LVP and Rigid Core
- Glue Down LVP*
- All Approved Floating Floors
- Vinyl Backed Carpet Tile
- Attached Pad Flooring

**Acrylic Pressure Sensitive Adhesives Only*

APPROVED SUBSTRATES:

- OSB
- Cured Concrete
- APA Approved Interior Subfloors

PRODUCT FEATURES:

- Sound Abatement
- Moisture Protection up to 85% RH
- LapWise™ Seam Sealing Technology
- Recyclable
- 20-Year Limited Warranty
- Made in the USA



ExxonMobil
Vistamaxx™
Performance Polymers



Wise Products, LLC

Website: www.WiseFlooringProducts.com

Phone: 615-847-2919

Fax: 615-847-2425

Email: Sales@WiseFlooringProducts.com

RATED RESIDENTIAL AND COMMERCIAL