

SoundWise™ PP 6012

PREMIUM MOISTURE CONTROL UNDERLAYMENT



SoundWise™ PP 6012 foam underlayment is our flagship underlayment. This supreme foam underlayment boasts a 99% RH for high moisture conditions. It can also be used on “green” concrete in those fast track production projects. SoundWise™ PP 6012 was designed to excel in high moisture content substrates.

APPLICATION: Approved for commercial and residential flooring.

DIMENSIONS AND PACKAGING:

- Roll Size = 100.1 sq ft
- Roll Dimensions = 42" x 28.6'

PHYSICAL PROPERTIES:

- Material = Polypropylene Foam (non-xlink)
- Density (lbs./cu ft) = 6.0
- Thickness (mm) = 1.2
- Compression Strength (psi@50%) = 20.2
- Moisture Vapor Emissions Rate = 0.00000338 (lbs/m2/24hrs)
- Joining System = LapWise™ Technology

INSTALLATION INSTRUCTIONS:

1. Clean, sweep or vacuum subfloor of all debris.
2. Check subfloor. Should be clean, dry and level.
3. Roll out underlayment to length of room.
4. If below grade, extend up the wall 2".
5. Roll out second row, overlap LapWise™ seam 2".
6. Remove release liner and press LapWise™ seam together.

SOUND TEST:

IIC	STC	DELTA	FLOOR	SUBFLOOR
66	63	26	LVP	6" CONCRETE W/ CEILING

APPROVED FOR USE UNDER:

- WPC, SPC, LVP and Rigid Core
- Glue Down LVP*
- All Approved Floating Floors

**Acrylic Pressure Sensitive Adhesives Only*

APPROVED SUBSTRATES:

- OSB
- Cured Concrete
- APA Grade Plywood
- APA Approved Interior Subfloors

PRODUCT FEATURES:

- Superior Sound Abatement
- Moisture Protection up to 99% RH
- LapWise™ Seam Sealing Technology
- Recyclable
- 20-Year Limited Warranty
- Made in the USA



ExxonMobil
Vistamaxx™
Performance Polymers



Wise Products, LLC

Website: www.WiseFlooringProducts.com

Phone: 615-847-2919

Fax: 615-847-2425

Email: Sales@WiseFlooringProducts.com

RATED RESIDENTIAL AND COMMERCIAL