

SoundWise™

PP 6012

PREMIUM MOISTURE CONTROL UNDERLAYMENT

PRODUCT FEATURES:



Sound Abatement



Moisture Protection



20-Year Limited Warranty



INSTALLATION INSTRUCTIONS:

1. Clean, sweep or vacuum subfloor of all debris.
2. Check subfloor. Should be clean, dry and level.
3. Roll out underlayment to length of room.
4. If below grade, extend up the wall 2".
5. Roll out second row, overlap LapWise™ seam 2".
6. Remove release liner and press LapWise™ seam together.



FLOAT IT



NAIL IT



GLUE IT

APPROVED FOR USE UNDER:

- WPC, SPC, LVP and Rigid Core
- Glue Down LVP*
- All Approved Floating Floors

**Acrylic Pressure Sensitive Adhesives Only*

APPROVED SUBSTRATES:

- OSB
- Cured Concrete
- APA Grade Plywood
- APA Approved Interior Subfloors



ExxonMobil
Vistamaxx™
Performance Polymers

Wise Products, LLC

Website: www.WiseFlooringProducts.com

Phone: 615-847-2919

Fax: 615-847-2425

Email: sales@wisemanufacturing.com

RATED RESIDENTIAL AND COMMERCIAL