

# SoundWise™ PP 4015

## LOW PROFILE UNDERLAYMENT



SoundWise™ PP 4015 is a low profile, waterproof foam underlayment. It is designed for use under a variety of flooring options: from traditional flooring to the new style of resilient floating floors. It offers excellent sound abatement and moisture protection.

**APPLICATION:** Approved for commercial and residential flooring.

### DIMENSIONS AND PACKAGING:

- Roll Size = 100.1 sq ft
- Roll Dimensions = 42" x 28.6'

### PHYSICAL PROPERTIES:

- Material = Polypropylene Foam (non-xlink)
- Density (lbs./cu ft) = 4.0
- Thickness (mm) = 1.5
- Compression Strength (psi@50%) = 16.1
- Moisture Vapor Emissions Rate = 0.00000338 (lbs/m2/24hrs)
- Joining System is LapWise™ Technology

### INSTALLATION INSTRUCTIONS:

1. Clean, sweep or vacuum subfloor of all debris.
2. Check subfloor. Should be clean, dry and level.
3. Roll out underlayment to length of room.
4. If below grade, extend up the wall 2".
5. Roll out second row, overlap LapWise™ seam 2".
6. Remove release liner and press LapWise™ seam together.

### SOUND TEST:

IIC	STC	DELTA	FLOOR	SUBFLOOR
66	63	26	LVP	6" CONCRETE w/ CEILING

### APPROVED FOR USE UNDER:

- Laminate
- WPC, SPC, LVP and Rigid Core
- Glue Down LVP
- Solid & Engineered Floating Floors

### APPROVED SUBSTRATES:

- OSB
- Cured Concrete
- APA Grade Plywood
- APA Approved Interior Subfloors

### PRODUCT FEATURES:

- Sound Abatement
- Moisture Protection up to 75% RH
- LapWise™ Seam Sealing Technology
- Recyclable
- 20-Year Limited Warranty
- Made in the USA



**ExxonMobil**  
Vistamaxx™  
Performance Polymers



# Wise Products, LLC

**Website:** [www.WiseFlooringProducts.com](http://www.WiseFlooringProducts.com)

**Phone:** 615-847-2919

**Fax:** 615-847-2425

**Email:** [Sales@WiseFlooringProducts.com](mailto:Sales@WiseFlooringProducts.com)

**RATED RESIDENTIAL AND COMMERCIAL**