


SoundWise™ MassBack™ SG

SINGLE GLUE UNDERLAYMENT



SoundWise™ MassBack™ SG is the first single glue LVP Underlayment in its class. It is specifically engineered to handle challenging fast-paced installations in high traffic or multi-family projects. This problem solving product is ideal for the quick and frequent flooring changes required in multi-family units.

APPLICATION: Approved for commercial and residential flooring.

DIMENSIONS AND PACKAGING:

- Roll Size: 100.1 sq ft

PHYSICAL PROPERTIES:

- Material = Thermoplastic olefin dispersed with calcium carbonate: one layer of point-bonded polypropylene.
- Density (lbs./cu ft) = 85.25
- Thickness (mm) = 0.75

INSTALLATION INSTRUCTIONS:

1. Clean sweep or vacuum subfloor of all debris.
2. Check the subfloor. It should be clean, dry and level.
3. Roll out the underlayment length of the room.
4. Line up seams close together; do not overlap.

SOUND TEST:

IIC	STC	DELTA	FLOOR	SUBFLOOR
65	61	21	LVP	6" CONCRETE W/ CEILING

APPROVED FOR USE UNDER:

- WPC, SPC, LVP and Rigid Core
 - Approved Floating Floors*
 - Attached Pad Flooring
- *Acrylic Pressure Sensitive Adhesives Only*

APPROVED SUBSTRATES:

- OSB
- Cured Concrete
- APA Approved Interior Subfloor

PRODUCT FEATURES:

- Sound Abatement
- Single Glue Installations
- 20-Year Limited Warranty
- Made in the USA



ExxonMobil
Vistamaxx™
Performance Polymers



Wise Products, LLC

RATED RESIDENTIAL AND COMMERCIAL

Website: www.WiseFlooringProducts.com

Phone: 615-847-2919

Fax: 615-847-2425

Email: Sales@WiseFlooringProducts.com